

Temperature Measuring & Disinfection Station

(FAST-Y-90S)

Technical Parameters

Models Technical Items Parameters	FAST-Y-90S-S	FAST-Y-90S-M	FAST-Y-90S-L
Dimensions (W×H×D)	600×2100×1500mm	2600m×2600×1500m	4500×2300×1500mm
Main Functions	Non-contact infrared temperature measurement & Hands disinfection & Sole disinfection	Non-contact infrared temperature measurement & Hands disinfection & Sole disinfection & Disinfection below the chest & Infrared start-stop spray	Non-contact infrared temperature measurement & Hands disinfection & Sole disinfection & Disinfection below the waist & Infrared start-stop spray & Facial recognition
Control Method	Manual	Manual; Wechat applet remote control	Manual; Wechat applet remote control; PC remote control
Electric Control Cabinet	Integrated type	Integrated type & Soft start	Integrated type & Soft start
PLC Module	Made in China	Siemens	Siemens
Equipment Shell	Galvanized steel sheet coated with anti-corrosion painting (Width: 0.8mm)	Aluminium alloy plate coated with anti-corrosion painting (Width: 1.5mm)	Aluminium alloy plate coated with anti-corrosion painting (Width: 1.5mm)
Lighting	LED lamp belt	LED tube	LED tube
Bottom Wheels	—	Universal wheels that can be locked	Universal wheel that can be locked
Anti-convection Windshield	—	Automatic ticket gate	Automatic ticket gate
Security inspection system	Metal detection device	Metal detection device	—
Total Weight (kg)	<150	<500	<800
Colors	Multi-scenario; Various styles	Multi-scenario; Various styles	Multi-scenario; Various styles
Lighting Window	—	Acrylic plate (Width: 10mm)	Acrylic plate (Width: 10mm)